



MACHINING CONDITIONS

APKT 160424 PDTR LT 3000 NEW

M0004029

Material Group	SAPPHIRE TOOLS	Material Example	Hardness	D.O.C		Feed			Vc		Advised D.O.C	Advised Feed	Advised Vc
				min[mm]	max[mm]	min[mm/t]	max[mm/t]	min[m/min]	max [m/min]	[mm]	[mm/t]	[m/min]	
Steel	Non Alloyed	1	C35, Ck45, 1020, 1045, 1060, 28Mn6	125 HB	0.5	15	0.18	0.32	190	330	5	0.23	250
				190 HB	0.5	15	0.18	0.32	190	300	5	0.23	220
				250 HB	0.5	15	0.18	0.32	190	250	5	0.23	200
	Low Alloyed	2	42CrMo4, St50, Ck60, 4140, 4340, 100Cr6	230 HB	0.5	15	0.15	0.25	150	210	5	0.2	180
				280 HB	0.5	15	0.15	0.22	130	190	5	0.18	150
				180 HB	0.5	15	0.15	0.25	150	240	5	0.2	200
				350 HB	0.5	15	0.15	0.22	130	170	5	0.18	140
	High Alloyed	3	X40CrMoV5, H13, M42, D3, S6-5-2, 12Ni19	220 HB	0.5	10.7	0.12	0.22	90	150	3.8	0.18	130
				280 HB	0.5	10.7	0.12	0.22	90	130	3.8	0.18	120
				320 HB	0.5	10.7	0.12	0.18	60	110	3.8	0.16	100
				350 HB	0.5	10.7	0.12	0.18	60	90	3.8	0.16	80
Stainless Steel	Austentic	4	304, 316, X5CrNi18-9	180 HB	0.5	15	0.15	0.25	190	250	5	0.2	220
				240 HB	0.5	15	0.12	0.22	160	210	5	0.2	190
	Duplex	5	X2CrNiN23-4, S31500	290 HB	0.5	10.7	0.12	0.18	70	130	3.8	0.16	100
	Ferritic & Martensitic			310 HB	0.5	10.7	0.12	0.18	70	120	3.8	0.16	90
Cast Iron	Grey	7	GG20, GG40, EN-GJL-250, N030B	200 HB	0.5	15	0.15	0.25	150	210	5	0.2	190
				42 HRc	0.5	10.7	0.15	0.2	90	150	3.8	0.16	130
				150 HB	0.5	15	0.18	0.32	150	240	5	0.23	200
	Malleable & Nodular	8	GGG40, GGG70, 50005	200 HB	0.5	15	0.18	0.32	150	220	5	0.23	180
				250 HB	0.5	15	0.18	0.32	150	190	5	0.23	160
NTI Alloys	Fe, Ni & Co Based	9	Incoloy 800	240 HB	0.5	10.7	0.12	0.18	30	50	3.8	0.16	32
			Inconel 700	250 HB	0.5	10.7	0.12	0.18	30	50	3.8	0.16	30
			Stellite 21	350 HB	0.5	10.7	0.12	0.18	30	50	3.8	0.16	30
	Ti Based	10	T40	-	0.5	10.7	0.12	0.18	30	60	3.8	0.16	40
Hardened Materials			TiAl6V4	-	0.5	10.7	0.12	0.2	40	70	3.8	0.18	55
	Steel Chilled Cast Iron White Cast Iron	11	G-X300CrMo15	55 HRc	0.5	1.6	0.1	0.14	30	60	1.3	0.12	40
			Ni-Hard 2	400 HB	0.5	4.3	0.1	0.18	40	80	1.9	0.14	50
			45 HRc	0.5	5.4	0.1	0.18	40	80	2.5	0.14	60	
			X100CrMo13, 440C, G-X260NiCr42	50 HRc	0.5	3.2	0.1	0.16	40	70	1.9	0.13	55
Aluminum	Al (>8%Si)	12	AlSi12	130 HB	0.5	15	0.18	0.32	200	400	5	0.25	280