



# MACHINING CONDITIONS

WNMP 060404 NN LT 1000

T0001954

| Material Group     | SAPPHIRE CUTTING TOOLS Group            | Material Example | Hardness                                | D.O.C   |         | Feed      |            | Amax   | Vc          |             | Advised D.O.C | Advised Feed | Advised Vc |     |
|--------------------|---|------------------|---|---------|---------|-----------|------------|--------|-------------|-------------|---------------|--------------|------------|-----|
|                    |   |                  |   | min[mm] | max[mm] | min[mm/t] | max [mm/t] | [mm^2] | min [m/min] | max [m/min] | [mm]          | [mm/t]       | [m/min]    |     |
| Steel              | Non Alloyed                             | 1                | C35, Ck45, 1020, 1045, 1060, 28Mn6      | 125 HB  | 0.3     | 3         | 0.11       | 0.23   | 0.6         | 180         | 330           | 2            | 0.18       | 300 |
|                    |   |                  |   | 190 HB  | 0.3     | 2.5       | 0.11       | 0.22   | 0.52        | 180         | 280           | 2            | 0.18       | 260 |
|                    |   |                  |   | 250 HB  | 0.3     | 2.5       | 0.11       | 0.2    | 0.48        | 180         | 250           | 2            | 0.18       | 240 |
|                    | Low Alloyed                             | 2                | 42CrMo4, St50, Ck60, 4140, 4340, 100Cr6 | 230 HB  | 0.3     | 2.5       | 0.1        | 0.2    | 0.48        | 120         | 250           | 2            | 0.14       | 240 |
|                    |   |                  |   | 280 HB  | 0.3     | 2         | 0.1        | 0.18   | 0.4         | 120         | 210           | 2            | 0.13       | 200 |
|                    |   |                  |   | 180 HB  | 0.3     | 2.5       | 0.1        | 0.2    | 0.5         | 120         | 280           | 2            | 0.14       | 260 |
|                    |   |                  |   | 350 HB  | 0.3     | 2         | 0.1        | 0.18   | 0.36        | 120         | 180           | 2            | 0.13       | 180 |
|                    | High Alloyed                            | 3                | X40CrMoV5, H13, M42, D3, S6-5-2, 12Ni19 | 220 HB  | 0.3     | 2.5       | 0.09       | 0.18   | 0.4         | 70          | 190           | 1.7          | 0.1        | 180 |
|                    |   |                  |   | 280 HB  | 0.3     | 2.5       | 0.09       | 0.16   | 0.4         | 70          | 150           | 1.7          | 0.1        | 140 |
|                    |   |                  |   | 320 HB  | 0.3     | 2         | 0.09       | 0.14   | 0.32        | 70          | 130           | 1.7          | 0.1        | 120 |
|                    |   |                  |   | 350 HB  | 0.3     | 2         | 0.09       | 0.14   | 0.26        | 70          | 110           | 1.7          | 0.1        | 110 |
| Stainless Steel    | Austentic                               | 4                | 304, 316, X5CrNi18-9                    | 180 HB  | 0.3     | 2.5       | 0.08       | 0.18   | 0.32        | 170         | 270           | 2            | 0.09       | 260 |
|                    |   |                  |   | 240 HB  | 0.3     | 2.5       | 0.08       | 0.18   | 0.26        | 160         | 220           | 2            | 0.08       | 210 |
|                    | Duplex                                  | 5                | X2CrNiN23-4, S31500                     | 290 HB  | 0.3     | 2         | 0.08       | 0.14   | 0.2         | 80          | 150           | 1.7          | 0.08       | 140 |
|                    |   |                  |   | 310 HB  | 0.3     | 2         | 0.08       | 0.14   | 0.2         | 70          | 140           | 1.7          | 0.08       | 140 |
|                    | Ferritic & Martensitic                  | 6                | 410, X6Cr17, 17-4 PH, 430               | 200 HB  | 0.3     | 2.5       | 0.08       | 0.18   | 0.32        | 170         | 250           | 1.7          | 0.09       | 240 |
| Cast Iron          | Grey                                    | 7                | GG20, GG40, EN-GJL-250, N030B           | 42 HRc  | 0.3     | 2         | 0.08       | 0.16   | 0.26        | 120         | 190           | 1.5          | 0.08       | 180 |
|                    |   |                  |   | 150 HB  | 0.3     | 3         | 0.08       | 0.2    | 0.64        | 170         | 250           | 2            | 0.18       | 240 |
|                    |   |                  |   | 200 HB  | 0.3     | 3         | 0.08       | 0.2    | 0.6         | 160         | 230           | 2            | 0.18       | 220 |
|                    | Malleable & Nodular                     | 8                | GGG40, GGG70, 50005                     | 250 HB  | 0.3     | 3         | 0.08       | 0.2    | 0.6         | 150         | 210           | 2            | 0.18       | 200 |
| NiTi Alloy         | Fe, Ni & Co Based                       | 9                | 150 HB                                  | 0.3     | 2.5     | 0.08      | 0.18       | 0.48   | 120         | 250         | 2             | 0.13         | 240        |     |
|                    |   |                  | 200 HB                                  | 0.3     | 2.5     | 0.08      | 0.18       | 0.4    | 120         | 230         | 2             | 0.13         | 220        |     |
|                    |   |                  | 250 HB                                  | 0.3     | 2.5     | 0.08      | 0.18       | 0.4    | 120         | 190         | 2             | 0.13         | 180        |     |
|                    | Ti Based                                | 10               | Incoloy 800                             | 240 HB  | 0.3     | 2         | 0.09       | 0.15   | 0.26        | 30          | 50            | 1.3          | 0.1        | 40  |
|                    |   |                  | Inconel 700                             | 250 HB  | 0.3     | 2         | 0.09       | 0.15   | 0.26        | 30          | 50            | 1.3          | 0.1        | 40  |
| Hardened Materials | Steel Chilled Cast Iron White Cast Iron | 11               | Stellite 21                             | 350 HB  | 0.3     | 2         | 0.09       | 0.15   | 0.26        | 20          | 50            | 1.3          | 0.1        | 35  |
|                    |   |                  | T40                                     | -       | 0.3     | 2         | 0.09       | 0.14   | 0.26        | 40          | 60            | 1.3          | 0.1        | 50  |
|                    |   |                  | TiAl6V4                                 | -       | 0.3     | 2         | 0.09       | 0.16   | 0.32        | 50          | 70            | 1.3          | 0.14       | 60  |
|                    |   |                  | G-X300CrMo15                            | 55 HRc  | 0.3     | 1.4       | 0.05       | 0.09   | 0.13        | 30          | 50            | 0.9          | 0.06       | 40  |
|                    |   |                  | Ni-Hard 2                               | 400 HB  | 0.3     | 1.6       | 0.05       | 0.12   | 0.17        | 40          | 60            | 1.1          | 0.1        | 50  |
| Aluminium          | Al (>8%Si)                              | 12               | X100CrMo13, 440C, G-X260NiCr42          | 45 HRc  | 0.3     | 1.8       | 0.05       | 0.12   | 0.2         | 50          | 100           | 1.4          | 0.1        | 90  |
|                    |   |                  |   | 50 HRc  | 0.3     | 1.5       | 0.05       | 0.1    | 0.17        | 40          | 90            | 1.1          | 0.08       | 80  |
|                    |   |                  |   | 55 HRc  | 0.3     | 1.4       | 0.05       | 0.09   | 0.13        | 40          | 80            | 0.9          | 0.06       | 70  |
|                    |   |                  | AlSi12                                  | 130 HB  | 0.3     | 4         | 0.1        | 0.3    | 0.7         | 200         | 400           | 2            | 0.23       | 350 |